

Promotes Adhesion of Asphaltic Patching

Bondade[®] is a solution of highly effective coupling agents designed to promote adhesion of asphaltic materials to a variety of substrates. The use of Bondade[®] markedly extends the service life of asphalt repairs.

Features and Advantages

- Bond Lasts Up to 85% Longer Than Current Methods
- Environmentally Safe
- Cost Effective
- Non-Flammable, Non-Combustible
- Contains No VOCs
- Will Not Irritate Skin
- Non-Toxic, Non-Hazardous Fumes
- No Smell, No Mess
- Easy Application. No Special Equipment Needed

*Evaluated, Proven and Continuously
Used by Many Agencies*



Applications

Bondade[®] is applied to the surface of the repair area prior to the asphalt mix. It may be applied to either dry or damp substrates after removing any loose debris from the repair area. It should not be applied to bare earth.

Preferred method of application is by spray, but brush application is also acceptable. For more information, please refer to the technical data sheet. Bondade[®] will enhance long-term durability on:

- Hot and Cold Patch Repairs
- Damp or Dry Holes
- Pavement Overlays
- Cold Joints
- Emergency Repairs



Physical Properties*

Property	Unit of Measure
Viscosity	16 sec (Zahn Cup #2)
Density	8.3 lbs/gal (1.0 gms/ml)
Appearance	Clear red tinted liquid
Wet Adhesion	Excellent
PH	6.0-7.0

* To be used as general guidelines only



Bondade[®] is available in 5 and 55 gallon containers.
*Trial size available for first time customers.